

Overview

Dimensions	481.4 x 480 x 132 mm (19 x 18.9 x 5.2")
------------	--

UniFi Application Suite

Protect	✓
---------	---

Access	✓
--------	---

Managed Cameras	(210) HD (140) 2K (70) 4K
-----------------	---------------------------------

Storage Capacity	(16) 3.5" drive bays
------------------	----------------------

Data Protection	✓
-----------------	---

Vantage Point	✓
---------------	---

Networking Interface	(2) 10G SFP+ (1) 10 GbE
----------------------	----------------------------

Power Redundancy	✓
------------------	---

Form Factor	Rack Mount (3U)
-------------	-----------------

Door Access Support	✓
---------------------	---

Hardware

Hard Drive Capacity	(16) 2.5/3.5" HDD / SSD support
---------------------	---------------------------------

Max. Power Budget for Drives	310W
------------------------------	------

Max. Power Consumption	410W
------------------------	------

Power Method	(2) AC input, 100—240V, 7A Max., 50/60Hz (Redundant, hot-swappable)
--------------	--

Power Supply	Hot-swappable 550W CRPS
--------------	-------------------------

Processor	8-core ARM® at 2.5 GHz
-----------	------------------------

Memory	32 GB
--------	-------

Management	Ethernet
------------	----------

Display	Bezel (Optional)
---------	------------------

Weight	Without rails: 16.6 kg (36.6 lb) With rails: 19.5 kg (43.0 lb)
Enclosure Material	SGCC steel
Mount Material	Aluminum
Slide Rails	482.6 mm (19") four-post racks Posts depths ranging from 650 to 1,000 mm (25.6–39.4")
Ambient Operating Temperature	-5 to 40° C (23 to 104° F)
Ambient Operating Humidity	5 to 95% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC