## Overview

Dimensions 137 x 40 x 26.4 mm

(5.4 x 1.6 x 1")

IR Night Vision 5 m (16 ft)

Smart Detections (People, Vehicles,

Animals)

 $\checkmark$ 

Resolution 5MP

Field of View H: 95.8°, V: 131.2°, D: 175.9°

Audio Two-way audio

Weatherproofing IPX5

Mounting Wall, 20° wedge (Included)

Gang box, junction box (Optional)

∧ Performance

Networking Interface 10/100 MbE port

Video

Image Settings

Color, brightness, sharpness, contrast, white balance, exposure control,

2DNR, 3DNR, NR by motion, masking, text overlay

Max. Frame Rate 24 FPS

Resolution 5MP 1920 x 2560 (3:4)

**Optics** 

Sensor 1/2.7" 5MP

Lens Fixed focal length

Night Mode Built-in IR LED illumination and IR cut filter

∧ Hardware

Max. Power Consumption 8W

Supported Voltage Range 37—57V DC

Power Method PoE

Processor Dual-core Arm® Cortex®-A7 based chip

Device: 142 g (5 oz)

Weight With flat wall mount: 165 g (5.8 oz)

With 20° wedge mount: 179 g (6.3 oz)

Enclosure Material Polycarbonate, metal

Mount Material Formed sheet metal

Button (1) Ring button (1) Factory-reset

Ambient Operating Temperature -30 to 50° C (-22 to 122° F)

Ambient Operating Humidity 20 to 90% noncondensing

NDAA Compliant

Certifications CE, FCC, IC