

Smoke and CO Alarm



Overview

Dimensions	Ø120 x 48.5 mm (Ø4.7 x 1.9")
Mounting	Wall and ceiling mount
UniFi Application Suite	Protect

Performance

Connectivity	SuperLink (Proprietary)
Operating frequency	US 915.6-927.6 MHz EU 865.1-869.5 MHz
Max. TX power	SuperLink 14 dBm
Max. range	SuperLink 2 km (1.2 mi)

Sensor Features

Smoke sensor	Yes
CO sensor	Yes
Alarm sound level	85 dB @ 3 m

Hardware

Max. power consumption	510 mW
Supported voltage range	3 V
Power method	(1) Replaceable lithium battery CR123A (SuperLink connectivity) (2) Non-replaceable lithium batteries L91 (Smoke & CO alarm)
Battery life	CR123A: Up to 10 years (SuperLink) L91: 10 years (Smoke & CO)
Weight	311 g (11 oz)
Enclosure material	Polycarbonate
Mount material	Polycarbonate
Buttons	(1) Function button (1) Factory reset (1) Test/silence button (1) Tamper switch (1) Deactivation switch
LEDs	(1) Status: B/W (1) Signal: B/R

Environment

Ambient operating temperature	0 to 40° C (32 to 104° F)
Ambient operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC, CAN/ULC 531, CSA 6.19, EN 14604, EN 50291-1, UL 217, UL 2034
NDAA compliant	Yes

Software

Web application	UniFi Protect
Mobile app	UniFi Protect iOS™ and Android™